Straight Through Quick-Connect Fittings

These couplers and plugs have no internal valves, providing maximum flow with minimum pressure drop. Supplied with Buna-N gasket seal. Interchange with Parker-Hannifin SST/BST, Foster FST and Hansen ST couplings.



Warning: Do Not Disconnect with pressure in line.

Body Size	NPT Thread Size	Material	Operating PSI	Part #	Price/Ea	Pkg Qty	Female Couplers
1/4"	1/4" - 18	brass	4500	STFC2	\$7.15	12	
3/8"	3/8" - 18	brass	2700	STFC3	8.45	12	
1/2"	1/2" - 14	brass	2500	STFC4	12.00	12	
3/4"	3/4" - 14	brass	2000	STFC6	19.80	12	
1"	1" - 11 1/2	brass	1000	STFC8	28.35	1	
1-1/4"	1-1/4" - 11 1/2	brass	800	STFC10	79.20	1	and him with the second states
1-1/2"	1-1/2" - 11 1/2	brass	600	STFC12	110.50	1	
2"	2" - 11 1/2	brass	400	STFC16	138.30	1	
1/4"	1/4" - 18	303 stainless	6700	STFC2SS	\$41.30	5	5 11
3/8"	3/8" - 18	303 stainless	5500	STFC3SS	51.70	5	
1/2"	1/2" - 14	303 stainless	3000	STFC4SS	61.80	5	
3/4"	3/4" - 14	303 stainless	3000	STFC6SS	115.00	5	
1"	1" - 11 1/2	303 stainless	1700	STFC8SS	156.00	5	

Body Size	NPT Thread Size	Material	Operating PSI	Part #	Price/Ea	Pkg Qty	Male Couplers
1/4" 3/8" 1/2" 3/4" 1" 1-1/4" 1-1/2" 2"	1/4" - 18 3/8" - 18 1/2" - 14 3/4" - 14 1" - 11 1/2 1-1/4" - 11 1/2 1-1/2" - 11 1/2 2" - 11 1/2	brass brass brass brass brass brass brass brass brass	4500 2700 2500 2000 1000 800 600 400	STMC2 STMC3 STMC4 STMC6 STMC8 STMC10 STMC12 STMC16	\$7.10 9.60 12.00 19.80 34.35 145.60 166.40 179.80	12 12 12 12 1 1 1 1 1	
1/4" 3/8" 1/2" 3/4" 1"	1/4" - 18 3/8" - 18 1/2" - 14 3/4" - 14 1" - 11 1/2	303 stainless 303 stainless 303 stainless 303 stainless 303 stainless	6700 5500 3000 3000 1700	STMC2SS STMC3SS STMC4SS STMC6SS STMC8SS	\$43.00 48.75 69.50 127.00 179.10	5 5 5 5 5	

Body Size	Hose I.D.	Material	Operating PSI *	Part #	Price/Ea	Pkg Qty	NEW Standard Hose Barbs
1/4"	1/4"	brass	5200	2ES2-B	\$6.70	100	
3/8"	3/8"	brass	2800	3ES3-B	7.90	50	
1/2"	1/2"	brass	2200	4ES4-B	11.15	25	
3/4"	3/4"	brass	1700	6ES6-B	17.45	20	
1"	1"	brass	1700	8ES8-B	26.60	10	

Operating pressures for the standard hose barbs utilizing hose barb end connections may be dramatically reduced SAFETY to that of the hose rating and/or hose and end connection combination. Consult hose manufacturer's catalog for ALERT hose end connection ratings. If in doubt, test under controlled conditions for suitability to application. Dixon Valve and Coupling cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.

Optional Pkg./Box Quantity Shown

Η

Straight Through Quick-Connect Fittings SAFETY

Warning: Do Not Disconnect with pressure in line.

Female Plugs	Body Size	NPT Thread Size	Material	Operating PSI	Part #	Price/Ea	Pk Qt
	1/4" 3/8" 1/2" 3/4" 1" 1-1/4" 1-1/2" 2"	1/4" - 18 3/8" - 18 1/2" - 14 3/4" - 14 1" - 11 1/2 1-1/4" - 11 1/2 1-1/2" - 11 1/2 2" - 11 1/2	steel steel steel steel steel steel steel	5000 3500 2700 2700 2000 1700 1400 600	STFP2 STFP3 STFP4 STFP6 STFP8 STFP10 STFP12 STFP16	\$3.15 3.55 4.95 8.35 21.85 55.15 62.40 93.60	12 12 12 12 12 12 12 12 12 12 12 12 12 1
	1/4" 3/8" 1/2" 3/4" 1"	1/4" - 18 3/8" - 18 1/2" - 14 3/4" - 14 1" - 11 1/2	brass brass brass brass brass	4500 2700 2200 1700 1000	STFP2B STFP3B STFP4B STFP6B STFP8B	\$2.95 3.75 5.50 9.10 17.50	12 12 12 12 12
	1/4" 3/8" 1/2" 3/4" 1"	1/4" - 18 3/8" - 18 1/2" - 14 3/4" - 14 1" - 11 1/2	303 stainless 303 stainless 303 stainless 303 stainless 303 stainless	6700 5500 3000 3000 1700	STFP2SS STFP3SS STFP4SS STFP6SS STFP8SS	\$11.00 14.00 29.15 44.00 89.00	5 5 5 5 5
Male Plugs	Body Size	NPT Thread Size	Material	Operating PSI	Part #	Price/Ea	Pk Qt
	1/4" 3/8" 1/2" 3/4" 1" 1-1/4" 1-1/2" 2"	1/4" - 18 3/8" - 18 1/2" - 14 3/4" - 14 1" - 11 1/2 1-1/4" - 11 1/2 1-1/2" - 11 1/2 2" - 11 1/2	steel steel steel steel steel steel steel	5000 3500 2700 2700 2000 1700 1400 600	STMP2 STMP3 STMP4 STMP6 STMP8 STMP10 STMP12 STMP16	\$3.25 3.40 4.75 7.30 14.85 45.80 62.40 73.35	12 12 12 12 12 12 1 1 1 1
	1/4" 3/8" 1/2" 3/4" 1"	1/4" - 18 3/8" - 18 1/2" - 14 3/4" - 14 1" - 11 1/2	brass brass brass brass brass	4500 2700 2200 1700 1000	STMP2B STMP3B STMP4B STMP6B STMP8B	\$2.75 3.20 5.10 8.05 17.25	12 12 12 12 12
EW	1/4" 3/8" 1/2" 3/4" 1"	1/4" - 18 3/8" - 18 1/2" - 14 3/4" - 14 1" - 11 1/2	303 stainless 303 stainless 303 stainless 303 stainless 303 stainless	6700 5500 3000 3000 1700	STMP2SS STMP3SS STMP4SS STMP6SS STMP8SS	\$10.95 12.00 27.25 43.20 92.00	5 5 5 5 5
Standard Hose Barbs	Body Size	Hose I.D.	Material	Operating PSI *	Part #	Price/Ea	Pk Qty
	1/4" 3/8" 1/2" 3/4" 1"	1/4" 3/8" 1/2" 3/4" 1"	brass brass brass brass brass brass	5200 2800 2200 1700 1700	E2S2-B E3S3-B E4S4-B E6S6-B E8S8-B	\$2.70 7.40 2.45 5.15 15.35	100 50 25 20 10
	1/4" 3/8" 1/2" 3/4" 1"	1/4" 3/8" 1/2" 3/4" 1"	steel steel steel steel steel	5500 4200 3500 2100 2000	E2S2 E3S3 E4S4 E6S6 E8S8	\$2.30 5.90 15.00 2.80 7.55	10 50 25 20 10

Coupling cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.

Optional Pkg./Box Quantity Shown

Flo-Mate Couplings

Flo-Mate Couplings offer maximum flow with an unrestricted flow path, permitting maximum temperature control and minimum coupling size. Plugs are designed short so that they can be easily recessed below a mold surface to avoid damage (when mold is changed or stored). Non-valved design should be used where maximum flow is needed and automatic shut-off is not required. Suitable for use with hot oil, water glycol and high temperature water.

- Socket seal is Viton[®]
- Service pressure is 200 PSI

- Sockets, sleeves and valves are brass.
- Sleeve spring and valve spring are 302 stainless steel.
- Locking balls are 404 stainless steel.

Sockets

(non-valved)

45° Stem



90° Stem Hose Shank

Straight Stem	
Hose Shank	

Size	Hose I.D.	Part #	Price/E	Pkg Qty
1/4"	1/4"	FMC204	\$6.95	10
1/4"	1/4"	FMC204L	7.75	10
1/4"	5/16"	FMC205~	7.60	10
1/4"	3/8"	FMC206	6.80	10
1/4"	3/8"	FMC206L	7.50	10
3/8"	3/8"	FMC306	9.30	5
3/8"	3/8"	FMC306L	9.90	5
3/8"	1/2"	FMC308	9.40	5
3/8"	1/2"	FMC308L	10.05	5
1/2"	1/2"	FMC504~	22.80	5
1/2"	1/2"	FMC504L	25.70	5
1/2"	3/4"	FMC506	23.00	5
1/2"	3/4"	FMC506L	28.05	5

Hose Shank							
Size	Hose I.D.	Part #	Price/E	Pkg Qty			
1/4"	1/4"	FMC224~	\$9.25	10			
1/4"	1/4"	FMC224L~	10.10	10			
1/4"	5/16"	FMC225~	9.10	10			
1/4"	3/8"	FMC226~	9.05	10			
1/4"	3/8"	FMC226L~	10.05	10			
3/8"	3/8"	FMC326~	12.30	5			
3/8"	3/8"	FMC326L~	13.30	5			
3/8"	1/2"	FMC328~	12.65	5			
3/8"	1/2"	FMC328L~	14.05	5			

Size	Hose I.D.	Part #	Price/E	Pkg Qty
1/4"	1/4"	FMC214	\$9.35	10
1/4"	1/4"	FMC214L~	9.80	10
1/4"	5/16"	FMC215~	9.40	10
1/4"	3/8"	FMC216	8.95	10
1/4"	3/8"	FMC216L~	9.70	10
3/8"	3/8"	FMC316~	12.50	5
3/8"	3/8"	FMC316L	13.10	5
3/8"	1/2"	FMC318	12.40	5
3/8"	1/2"	FMC318L~	13.55	5

"L" denotes push-on hose barb end

Plugs



Female NPT (steel)					Male NPT (brass)				
Size	Thread	Part #	Price/Ea	Pkg Qty	Size	Thread	Part #	Price/Ea	Pkg Qty
1/4"	1/8"	FMP251F~	\$2.05	25	1/4"	1/8"	FMP251	\$1.30	25
1/4"	1/4"	FMP252F~	2.20	25	1/4"	1/4"	FMP252	1.50	25
1/4"	3/8"	FMP253F~	3.00	25	1/4"	3/8"	FMP253	1.90	25
3/8"	1/4"	FMP352F	1.80	25	3/8"	1/4"	FMP352	1.60	25
3/8"	3/8"	FMP353F	2.10	25	3/8"	3/8"	FMP353	1.70	25
3/8"	1/2"			25	3/8"	1/2"	FMP354	3.50	25
1/2"	1/2"			25	1/2"	1/2"	FMP554	4.45	25
1/2"	3/4"			25	1/2"	3/4"	FMP556	6.50	25

Warning:

Over-pressurization could result in a sudden failure of the coupling causing severe bodily injury or death. ALERT Be sure to select the proper coupling for your application and use it only within the specified service pressure ranges.

Couplings do wear out. In order to avoid severe bodily injury or death, couplings must be routinely checked for condition and replaced if necessary.

Optional Pkg./Box Quantity Shown

SAFETY

Flow Control Valves Series F

,	
	Lot want

Thread	Part #	Price/Ea
1/8"	SFC200	\$47.20
1/4"	SFC400	53.20
3/8"	SFC600	65.75
1/2"	SFC800	88.55
3/4"	SFC1200	126.25

Two-step needle provides fine adjustments at low flow with the first three turns of the adjusting knob. The next three turns give full-open needle position and conventional throttling control. When flow is reversed, the heavy-duty poppet/retainer permits full-flow return capacity. Exclusive color-coded reference scale on the adjusting knob greatly simplifies flow setting, resetting, adjusting and return to an original flow. A simple set screw locks the valve on any desired setting.

Maximum operating pressure:

black oxide steel - 5000 PSI for 1/8" - 1/2", 3000 PSI for 3/4" Also available in brass, see page 95



Thread	Part #	Price/Ea
1/4"	SPF400	\$37.30
3/8"	SPF600	49.45
1/2"	SPF800	64.40

Utilizes a ball type check that meters the flow of hydraulic oil in one direction and allows for free flow in the reverse direction. Recommended for use in non-shock applications.

· Maximum operating pressure: zinc plated steel with a Dichromate seal - 5000 PSI, 5 PSI cracking pressure Also available in brass, see page 95

Series N

Series PF

	Thread	Part #	Price/Ea
	1/8"	SN200	\$48.60
	1/4"	SN400	55.30
and the second se	3/8"	SN600	66.50
A 2000 Pist	1/2"	SN800	85.30
STOR M	3/4"	SN1200	113.45

Ideal for use as speed controls on hydraulic systems where a reverse flow check valve is not needed. Provides excellent control and reliable shutoff in a very small envelope. Colorcoded reference scale on the adjusting knob simplifies setting, resetting, adjusting and quick return to a previous speed setting.

Maximum operating pressure: steel - 5000 PSI

Also available in brass, see page 95



Series MV

Thread	Part #	Price/Ea
1/4"	SMV400	\$54.95
3/8"	SMV600	73.45
1/2"	SMV800	97.40

With these high-precision metering and shutoff valves, you can readily make fine adjustments and reset with the exclusive color code 5000 that shows when you reach the desired setting.

Body components are precision-turned from solid barstock

- All models have 416 stainless steel needles
- Maximum operating pressure: steel 5000 PSI



Series C Check Valves

Free Price/ Thread Part # Flow Ea GPM SCV200 3 \$39.95 1/8" 1/4" SCV400 5 40.65 3/8" SCV600 47.30 8 1/2" SCV800 15 54.80

Provides free flow in one direction and dependable shutoff in the opposite direction.

Maximum operating pressure:

Steel - 5000 PSI, 5 PSI cracking pressure

Also available in brass, see page 94

High Pressure Full-Bore Ball Valves

- Blow out proof stem
- Rugged carbon steel construction
- Viton[®] shaft seals
- Female NPTF
- Also available in: Stainless steel

SAE ORB thread

NPTF Thread	Part #	Working Pressure	Price/Ea
1/4"	HPBV25	7350	\$48.70
3/8"	HPBV38	7350	51.40
1/2"	HPBV12	7350	55.80
3/4"	HPBV34	5880	113.90
1"	HPBV10	5145	134.65
11⁄4"	HPBV125	6175	340.70
11⁄2"	HPBV150	6175	406.00
2"	HPBV200	6175	604.20



Mini Needle Valves

Mini needle valves are available in a variety of materials, and handle options. All are equipped with both a Viton[®] O-ring seal and a Teflon[®] back-up ring below the threads to protect the mini valve from corrosion and galling. The stem threads are rolled for strength and ease of operation, and the metal-to-metal hard seat design is 100% helium leak tested to 1 x 10^4 ml/s at 200 PSI on each mini valve.

- Orifice size: 0.172"
- Flow coefficient: 0.42
- O-ring seal: Viton[®]
- Back-up ring: Teflon[®]

NPT Thread Size	Handle Style	Material	Operating PSI	Part #	Price/Ea	Male to Female
1/8" - 27 1/4" - 18	knurled knob knurled knob	brass brass	3000 3000	MFB101 MFB102	\$31.55 31.55	
1/8" - 27 1/4" - 18	T design T design	nickel plated steel nickel plated steel	6000 6000	MFC101 MFC102	\$34.90 34.90	
1/8" - 27 1/4" - 18	T design T design	316 stainless steel 316 stainless steel	6000 6000	MFS101~ MFS102	\$84.40 84.40	

NPT Thread Size	Handle Style	Material	Operating PSI	Part #	Price/Ea	F	Female to Female
1/8" - 27 1/4" - 18	knurled knob knurled knob	brass brass	3000 3000	FFB101 FFB102	\$31.55 31.55		
1/8" - 27 1/4" - 18	T design T design	nickel plated steel nickel plated steel	6000 6000	FFC101 FFC102	\$34.90 34.90	<u>III</u>	
1/8" - 27 1/4" - 18	T design T design	316 stainless steel 316 stainless steel	6000 6000	FFS101 FFS102	\$84.40 84.40		

Industrial Hydraulic Quick-Connect Fittings

All Industrial Fittings are female NPTF

The Industrial Quick Connect Series features poppet style shut-off valves in both the coupler and the plug.

- These valves are designed to prevent fluid loss when the coupler is disconnected. •
- Interchangeable with Parker-Hannifin 60 series •
- Meets dimensional requirements of Series B in ISO 7241-1 •
- Seal material is Buna-N •

Poppet Valve Coupler

· Contact factory if you intend to use on a compressed air system



Body Size	NPTF Thread Size	Material	Operating PSI	Part #	Price/Ea	Pkg Qty
1/4"	1/4" - 18	steel	5000	16-263	\$19.15	5
3/8"	3/8" - 18	steel	4000	16-363	25.40	5
1/2"	1/2" - 14	steel	4000	16-463	32.50	5
3/4"	3/4" - 14	steel	2500	16-663	50.40	5
1"	1" - 11 1/2	steel	2000	16-863	69.40	5
1/4"	1/4" - 18	brass	1000	B16-263	\$20.20	5
3/8"	3/8" - 18	brass	1000	B16-363	25.90	5
1/2"	1/2" - 14	brass	1000	B16-463	39.65	5
3/4"	3/4" - 14	brass	1000	B16-663	63.95	5
1"	1" - 11 1/2	brass	1000	B16-863	90.55	5
1/4"	1/4" - 18	303 stainless	2000	SS16-263	\$58.00	5
3/8"	3/8" - 18	303 stainless	1500	SS16-363	81.15	5
1/2"	1/2" - 14	303 stainless	1500	SS16-463	104.15	5
3/4"	3/4" - 14	303 stainless	1500	SS16-663	184.55	5
1"	1" - 11 1/2	303 stainless	1000	SS16-863	311.20	5

Poppet Valve Plug	Body Size	NPTF Thread Size	Material	Operating PSI	Part #	Price/Ea	Pkg Qty
	1/4" 3/8" 1/2" 3/4" 1" 1/4"	1/4" - 18 3/8" - 18 1/2" - 14 3/4" - 14 1" - 11 1/2 1/4" - 18	steel steel steel steel brass	5000 4000 2500 2000 1000	17-263 17-363 17-463 17-663 17-863 B17-263	\$8.20 12.45 13.90 20.60 28.50 \$9.70	5 5 5 5 5 5
and Fur	3/8" 1/2" 3/4" 1"	3/8" - 18 1/2" - 14 3/4" - 14 1" - 11 1/2	brass brass brass brass	1000 1000 1000 1000	B17-363 B17-463 B17-663 B17-863	11.40 16.25 23.35 33.10	5 5 5 5
	1/4" 3/8" 1/2" 3/4" 1"	1/4" - 18 3/8" - 18 1/2" - 14 3/4" - 14 1" - 11 1/2	303 stainless 303 stainless 303 stainless 303 stainless 303 stainless	2000 1500 1500 1500 1500 1000	SS17-263 SS17-363 SS17-463 SS17-663 SS17-863	\$25.15 34.80 48.90 89.65 145.05	5 5 5 5 5

Optional Pkg./Box Quantity Shown

See Hydraulic Profile Chart on page 463.

Industrial Hydraulic Quick-Connect Fittings

Body Size	Material	Part #	Price / Each	Pkg Qty		Dust Plugs
1/4" 3/8" 1/2" 3/4" 1"	rubber rubber rubber rubber rubber rubber	16-002 16-003 16-004 16-006 16-008	\$2.95 3.40 3.85 7.35 8.30	5 5 5 5 5		
1/4" 3/8" 1/2" 3/4" 1"	auminum aluminum aluminum aluminum aluminum	16-002A 16-003A 16-004A 16-006A 16-008A	\$9.10 10.00 11.60 15.90 43.65	5 5 5 5 5	rubber	aluminum
Body Size	Material	Part #	Price / Each	Pkg Qty		Dust Caps
1/4" 3/8" 1/2" 3/4"	rubber rubber rubber rubber	17-002 17-003 17-004 17-006	\$3.00 3.35 3.70 8.20	5 5 5 5	\cap	0
1"	rubber	17-008	8.30	5		

3000 Series Hydraulic Quick-Connect Fittings

The 3000 series interchanges with Parker 3000, Bruning IP 370 and Enerpac C 604. Threaded union locking system and precision ball-type check valves are designed for extreme high pressure applications such as hydraulic rams and pumps where low flow and pressures up to 10,000 PSI are encountered. Seals are polyurethane.

Body Size	NPT Thread Size	Material	Operating PSI	Part #	Price/Ea	Pkg Qty	Couplers
1/4"	1/4" - 18 M	steel	10,000	30-200	\$28.50	5	
3/8"	3/8" - 18 M	steel	10,000	30-300	29.95	5	And A
3/8"	3/8" - 18 F	steel	10,000	30-300F	32.10	5	Treasure and the second se
I					,		

Body Size	NPT Thread Size	Material	Operating PSI	Part #	Price/Ea	Pkg Qty	Plugs
1/4"			-,				
3/8"	3/8" - 18	steel	10,000	31-300	17.00	5	And a second

Body Size	NPT Thread Size	Material	Part #	Price/Ea	Pkg Qty	Screw type Dust Plugs
1/4"	1/4" - 18	steel	30-200DP	\$6.10	5	
3/8"	3/8" - 18	steel	30-300DP	6.45	5	

Body Size	NPT Thread Size	Material	Part #	Price/Ea	Pkg Qty	Screw type Dust Caps
1/4" 3/8"	1/4" - 18 3/8" - 18	steel steel	31-200DC 31-300DC	\$8.95 8.95	5 5	
	See Hydraul	ic Profile Cl	nart on pages 4	163 and 464	4.	

Agricultural Hydraulic Quick-Connect Fittings

The Agricultural Quick-Connect features ball style shut-off valves in both the coupler and the plug. The International Standard Organization (ISO) has adopted specifications regarding dimensions and interchangeability. Agricultural series couplers are used on construction equipment, farm implements and most other mobile equipment. Interchangeable with Pioneer 4000 series, Safeway Agricultural series and ISO C.

FTP Ball Valve Couplers	Body Size	NPTF Thread Size	Material	Operating PSI	Part #	Price / Ea	Pkg Qty
/1777TE	1/4"	1/4" - 18	steel	2500	18-200 *	\$19.00	5
and the second s	3/8"	3/8" - 18	steel	2500	18-300 *	23.95	5
	1/2"	1/2" - 14	steel	2500	18-400	19.90	5
	1/2"	3/4" - 14	steel	2500	18-600	29.40	5
	3/4"	3/4" - 14	steel	2500	18-660	59.10	5
i de la companya de la	1"	1" - 11 1/2	steel	2500	18-800 *	84.10	5

* Have a poppet valve design with a soft seat

FTP Ball Valve Plugs	Body Size	NPTF Thread Size	Material	Operating PSI	Part #	Price / Ea	Pkg Qty
	1/4"	1/4" - 18	steel	2500	19-200 *	\$9.60	10
	3/8"	3/8" - 18	steel	2500	19-300 *	12.05	10
	1/2"	1/2" - 14	steel	2500	19-400	9.60	10
Comment of the local division of the local d	1/2"	3/4" - 14	steel	2500	19-600	15.65	10
And	3/4"	3/4" - 14	steel	2500	19-660	15.60	10
	1"	1" - 11 1/2	steel	2500	19-800 *	37.85	10

* Have a poppet valve design with a soft seat

ORB Ball Valve Coupler	Body Size	ORB Thread Size	Material	Operating PSI	Part #	Price / Ea	Pkg Qty
	1/2"	3/4" - 16	steel	2500	18-415	\$24.45	5

ORB Ball Valve Plug Body Size ORB Thread Size			Material	Operating PSI	Part #	Price / Ea	Pkg Qty
and divine Ca	1/2"	3/4" - 16	steel	2500	19-415	\$11.10	5

Optional Pkg./Box Quantity Shown

See Hydraulic Profile Chart on page 463.

Agricultural Series Dust Plugs and Caps

Body Size	Material	Part #	Price / Ea	Pkg Qty
1/4" 3/8" 1/2" 3/4" 1"	rubber rubber rubber rubber rubber	18-002 18-003 18-004 18-006 18-008	\$3.80 8.25 7.25 8.20 9.40	10 10 10 10 10
Body Size	Material	Part #	Price / Ea	Pkg Qty
1/4" 3/8" 1/2" 3/4" 1"	rubber rubber rubber rubber rubber	19-002 19-003 19-004 19-006 19-008	\$3.95 4.55 4.25 11.40 13.05	10 10 10 10 10
	Size 1/4" 3/8" 1/2" 3/4" 1" Body Size 1/4" 3/8" 1/2" 3/4" 1/2" 3/4" 1/2" 3/4" 1/2"	SizeMaterial1/4"rubber3/8"rubber1/2"rubber3/4"rubber1"rubber1"rubber80dy SizeMaterial1/4"rubber3/8"rubber1/2"rubber3/4"rubber	Size Material Part # 1/4" rubber 18-002 3/8" rubber 18-003 1/2" rubber 18-004 3/4" rubber 18-006 1" rubber 18-004 3/4" rubber 18-006 1" rubber 18-008	Size Material Part # Price / Ea 1/4" rubber 18-002 \$3.80 3/8" rubber 18-003 8.25 1/2" rubber 18-004 7.25 3/4" rubber 18-006 8.20 1" rubber 18-006 8.20 1" rubber 18-008 9.40

7800 Series Hydraulic Thread-to-Connect Fittings

The 7800 series interchanges with Aeroquip 5100 series, Parker 6100 series and Snap-Tite 78 series. Designed for applications requiring a heavy duty coupling that can be connected under pressure with minimum spillage and air inclusion. Widely used on dump trailer wet-line hydraulic systems and oil field equipment. Not recommended for continuous hydraulic impulse applications.

Body Size	NPT Thread Size	Body	Material Nut	Operating PSI	Part #	Price / Each	Pkg Qty	Couplers with Wing Nut
3/4" 1" 1-1/4" 1-1/2"		brass brass	malleable iron malleable iron	3000 2750	78-600 78-800 78-1000 78-1200	\$63.15 76.00 135.05 177.00	5 5 5 1	

Body Size	NPT Thread Size	Material	Operating PSI	Part #	Price / Each	Pkg Qty	Plugs
3/4"	3/4" - 14	brass	3000	79-600	\$41.60	5	
1"	1" - 11 1/2	brass	3000	79-800	50.20	5	
1-1/4"	1-1/4" - 11 1/2	brass	2750	79-1000	106.40	5	
1-1/2"	1-1/2" - 11 1/2	brass	2750	79-1200	170.20	1	

Body Size	Material	Part #	Price / Each	Pkg Qty	Flanges
3/4"	steel	77-600	\$3.20	2	
1"	steel	77-800	4.35	2	
1-1/4"	steel	77-1000	5.50	2	
1-1/2"	steel	77-1200	6.95	2	

Optional Pkg./Box Quantity Shown

7800 Series Dust Plugs and Caps

Dust Plugs	Pkg Qty	Price / Ea	Part #	Material	Body Size
	1	\$14.55 17.35	78-006 78-008	brass brass	3/4" 1"
	1 1	23.20 41.00	78-010 78-012	brass brass	1-1/4" 1-1/2"

Body Size	Material	Part #	Price / Ea	Pkg Qty	Dust Caps
3/4"	brass	79-006	\$12.80	1	
1"	brass	79-008	15.25	1	
1-1/4"	brass	79-010	21.60	1	
1-1/2"	brass	79-012	37.95	1	and the second s

See Hydraulic Profile Chart on page 464.

Η

5600 Series Hydraulic Quick-Connect Fittings

The 5600 series is interchangeable with the Aeroquip 5600, Parker 6600, and ISO A interchange. The two-way check valves in the plug and socket automatically balance in flow position and provide instant shut off when disconnected. To connect, simply retract sleeve, insert plug, and release sleeve. Locks automatically, providing positive pressure tight connection. Permits fast connection and disconnection of gas or fluid lines with minimal loss of media from either end. Full 360° swivel action prevents hose kinking and twisting. Non-valved, slotted valve and straight through units available on request.

Couplers	Body Size	NPT Thread Size	Material	Operating PSI	Part #	Price / Ea	Pkg Qty
	1/4"	1/8" - 27	steel	5000	56-100	\$29.35	5
	1/4"	1/4" - 18	steel	5000	56-200	25.25	5
Concession of the local division of the loca	3/8"	3/8" - 18	steel	4000	56-300	30.25	5
	1/2"	1/2" - 14	steel	4000	56-400	31.50	5
	1/2"	3/4" - 14	steel	4000	56-600	39.50	5
	3/4"	3/4" - 14	steel	4000	56-660	60.00	5
	1"	1" - 11 1/2	steel	4000	56-800	75.70	5

Plugs	Body Size	NPT Thread Size	Material	Operating PSI	Part #	Price / Ea	Pkg Qty
	1/4"	1/8" - 27	steel	5000	57-100	\$9.85	5
	1/4"	1/4" - 18	steel	5000	57-200	9.70	5
A STATE AND A DESCRIPTION OF	3/8"	3/8" - 18	steel	4000	57-300	14.60	5
VP	1/2"	1/2" - 14	steel	4000	57-400	14.20	5
	1/2"	3/4" - 14	steel	4000	57-600	24.65	5
	3/4"	3/4" - 14	steel	4000	57-660	32.55	5
A second s	1"	1" - 11 1/2	steel	4000	57-800	33.00	5

Optional Pkg./Box Quantity Shown

See Hydraulic Profile Chart on page 463.

5600 Series Dust Plugs and Caps

Dust Plugs	Body Size	Material	Part #	Price / Each	Pkg Qty
	1/4"	rubber	56-002	\$4.35	5
	3/8"	rubber	56-003	4.55	5
	1/2"	rubber	56-004	4.50	5
	3/4"	rubber	56-006	10.65	5
	1"	rubber	56-008	12.35	5
Dust Caps	Body Size	Material	Part #	Price / Each	Pkg Qty
	1/4"	rubber	57-002	\$4.35	5
	3/8"	rubber	57-003	4.55	5
	1/2"	rubber	57-004	4.75	5
	3/4"	rubber	57-006	10.65	5
	1"	rubber	57-008	12.05	5

VH Series Hydraulic Quick-Connect Fittings

General purpose hydraulic quick-connect provides superior flow characteristics with built-in reliability. Standard seal is Buna-N. VH Series interchanges with Snap-tite H Series.

Couplers	Pkg Qty	Price/Ea	Part #	Operating PSI	Material	NPT Thread Size	Body Size
	5 5 5	\$15.85 21.55 26.20	VHC200 VHC300 VHC400	6500 4500 4000	zinc plated steel zinc plated steel zinc plated steel	1/4" - 18 3/8" - 18 1/2" - 14	1/4" 3/8" 1/2"
	5 5 1 1	40.60 63.00 146.55 206.35	VHC600 VHC800 VHC1000 VHC1200	3500 2000 1750 1500	zinc plated steel zinc plated steel zinc plated steel zinc plated steel	3/4" - 14 1" - 11 1/2 1-1/4" - 11 1/2 1-1/2" - 11 1/2	3/4" 1" 1-1/4" 1-1/2"
	1 5 5 5	392.40 \$18.05 23.45 34.40	VHC1600 VHC200B VHC300B VHC400B	1500 2250 2250 2000	zinc plated steel brass brass brass brass	2" - 11 1/2 1/4" - 18 3/8" - 18 1/2" - 14	2" 1/4" 3/8" 1/2"
Plugs	Pkg Qty	Price/Ea	Part #	Operating PSI	Material	NPT Thread Size	Body Size
	5 5 5 5 5 1 1 1	\$10.90 13.50 16.15 24.20 38.70 114.90 146.65 283.70	VHN200 VHN300 VHN400 VHN600 VHN800 VHN1000 VHN1200 VHN1600	6500 4500 3500 2000 1750 1500 1500	zinc plated steel zinc plated steel	1/4" - 18 3/8" - 18 1/2" - 14 3/4" - 14 1" - 11 1/2 1-1/4" - 11 1/2 1-1/2" - 11 1/2 2" - 11 1/2	1/4" 3/8" 1/2" 3/4" 1" 1-1/4" 1-1/2" 2"
	5	\$12.90	VHN200B	2250	brass	1/4" - 18	1/4"

Optional Pkg./Box Quantity Shown

See Hydraulic Profile Chart on page 464.

VH Series Dust Plugs and Caps

Body Size	Material	Part #	Price / Each	Pkg Qty		Dust Plugs
1/4"	rubber	VHC002	\$4.55	10		
3/8"	rubber	VHC003	4.55	10		
1/2"	rubber	VHC004	4.95	10		
3/4"	rubber	VHC006	4.95	10		A REAL PROPERTY
1"	rubber	VHC008	9.20	10		
1-1/4"	aluminum	VHC010	52.30	10		
1-1/2"	aluminum	VHC012	107.00	10		
2"	aluminum	VHC016	182.40	10	rubber	aluminum

Body Size	Material	Part #	Price / Each	Pkg Qty		Dust Caps
1/4"	rubber	VHN002	\$4.55	10		
3/8"	rubber	VHN003	4.55	10		
1/2"	rubber	VHN004	4.95	10	\frown	
3/4"	rubber	VHN006	4.95	10		K Diana
1"	rubber	VHN008	9.20	10		
1-1/4"	aluminum	VHN010	65.05	10		
1-1/2"	aluminum	VHN012	124.80	10		
2"	aluminum	VHN016	156.95	10	rubber	aluminum

Flush Face Hydraulic Quick-Connect Fittings

Flush Face interchanges with Aeroquip FD89, Parker FE, Snap-tite 74, Faster FF and Holmbury Series A. Flush face valve design minimizes fluid loss resulting in a cleaner, safer work environment. Automatic, push-to-connect couplings provide high flow with low pressure drop assuring maximum hydraulic tool performance. To reduce the possibility of accidental disconnect, a sleeve lock safety feature requires turning the collar to unlock the coupling. Conforms to ISO16028 interchange standard. Operating pressure is **5,000 PSI**.

Couplers	Body Size	NPTF Thread Size	Material	Operating PSI	Part #	Price / Each	Pkg Qty
	1/4" 3/8 " 3/8" 1/2" 1/2" 5/8"	1/4" - 18 3/8" - 18 1/2" - 14 1/2" - 14 3/4" - 14 3/4" - 14	steel steel steel steel steel steel	5000 5000 5000 5000 5000 5000	2HTF2 3HTF3 3HTF4 4HTF4 4HTF6 5HTF6	\$55.05 55.05 55.05 66.75 68.70 92.20	5 5 5 5 5 5 5 5 5
	3/4" 1"	3/4" - 14 1" - 11 1/2	steel	5000 5000	6HTF6 8HTF8	133.00 222.40	5 5
Plugs	Body Size	NPTF Thread Size	Material	Operating PSI	Part #	Price / Each	Pkg Qty
	1/4" 3/8" 3/8" 1/2" 1/2" 5/8" 3/4" 1"	1/4" - 18 3/8" - 18 1/2" - 14 1/2" - 14 3/4" - 14 3/4" - 14 3/4" - 14 1" - 11 1/2	steel steel steel steel steel steel steel steel	5000 5000 5000 5000 5000 5000 5000 500	HT2F2 HT3F3 HT3F4 HT4F4 HT4F6 HT5F6 HT6F6 HT8F8	\$32.80 21.70 21.70 39.30 41.25 52.75 85.20 121.60	5 5 5 5 5 5 5 5 5 5 5
SAE/ORB Coupler	Body Size	ORB Thread Size	Material	Operating PSI	Part #	Price / Each	Pkg Qty
	1/2"	7/8" - 14	steel	5000	4HTOF5	\$67.55	5
SAE/ORB Plug	Body Size	ORB Thread Size	Material	Operating PSI	Part #	Price / Each	Pkg Qty
	1/2"	7/8" - 14	steel	5000	HT4OF5	\$41.25	5

Optional Pkg./Box Quantity Shown

See Hydraulic Profile Chart on page 464.

Flush Face Series Rubber Coupler and Nipple Caps

Coupler Caps	Body Size	Material	Part #	Price / Each	Pkg Qty
	3/8 "	rubber	3HTDP	\$2.90	10
	1/2"	rubber	4HTDP	3.85	10
	5/8"	rubber	5HTDP	4.70	10
	3/4"	rubber	6HTDP	4.85	10
	1"	rubber	8HTDP	5.55	10

Nipple Caps	Body Size	Material	Part #	Price / Each	Pkg Qty
	3/8"	rubber	HT3DC	\$2.90	10
	1/2"	rubber	HT4DC	3.85	10
	5/8"	rubber	HT5DC	4.70	10
	3/4"	rubber	HT6DC	4.80	10
	1"	rubber	HT8DC	5.40	10

Hydraulic Water-Blast Quick Couplers NEW

- Plug mounted sleeve guard protects against accidental • disconnection.
- Smooth bore full-flow design ensures maximum flow with minimal pressure drop
- Heavy duty knurled sleeve with locking pin provides • maximum protection against brinneling and accidental disconnection
- Steel body components maximize service life by resisting the effects of brinneling and internal erosion.

1/2" 3/8" - 18 steel 10000 4EAF3 \$87.75 25	Coup	Pkg Qty	Price / Each	Part #	Operating PSI	Material	NPTF Thread Size	Body Size
$1/2^{"}$ $1/2^{"} - 14$ STAAL 10000 $4FAFA$ $8/75$ 25		25 25	\$87.75 87.75	4EAF3 4EAF4	10000 10000	steel steel	3/8" - 18 1/2" - 14	1/2" 1/2"



	Plug	Pkg Qty	Price / Each	Part #	Operating PSI	Material	NPTF Thread Size	Body Size
" 1/2" - 14 steel 10000 EA4F4 21.70 25		-		-				1/2" 1/2"

Hydraulic Suction and Return Line Hose Fittings

For SAE100R4 Hydraulic Hose

- · Designed and machined for hydraulic suction line applications.
- Barbs provide easy assembly and maximum gripping action.
- Plated steel



Male Pipe NPTF



SAE (JIC) 37° Swivel

Hose I.D.	Thread NPTF	Part #	Price/Ea	Hose I.D.	Thread	Part #	Price/Ea
3/4"	3/4" - 14	188-12	\$11.50	3/4"	1-1/16" - 12	688-12	\$18.70
1"	1" - 11 1/2	188-16	18.40	1"	1-5/16" - 12	688-16	26.00
1-1/4"	1-1/4" - 11 1/2	188-20	29.60	1-1/4"	1-5/8" - 12	688-20	33.35
1-1/2"	1-1/2" - 11 1/2	188-24	38.65	1-1/2"	1-7/8" - 12	688-24	49.00
2"	2" - 11 1/2	188-32	75.70	2"	2-1/2" - 12	688-32	98.65

Return line clamps must be used with these fittings.

SAFETY ALERT

Hydraulic Return Line Clamps

		(zinc plat	ted malleable irc	on)	
Hose I.D.	Clamp Range	Part #	Price / Each	Pky Qty	Torque *
3/4" 1" 1-1/4" 1-1/2"	1-8/64" - 1-12/64" 1-40/64" - 1-52/64" 1-48/64" - 2-3/64" 2-7/64" - 2-19/64"	J48 DL14 DL20 DL24	\$4.30 7.75 7.70 7.70	100 25 25 25	15 40 27 27
2"	2-20/64" - 2-40/64"	DL32	9.00	25	40



* Torque values for clamps are based on "dry bolts".

The use of lubricant on bolts will adversely effect clamp performance.

Optional Pkg./Box Quantity Shown

Hydraulic Hose Couplings

Stems

	E.	1700	411	A P TO	100
	21.7	1212		1	
100000	1000		111	110	

Plated Steel Stems			Plated Iron Stems		
NPTF Size	Plated Steel Part #	Price / Each	NPTF Size	Plated Iron Part #	Price / Each
3/8" 1/2" 3/4" 1"	MSC HY4 MS6 HY8	\$3.80 8.95 6.40 12.60	1-1/4" 1-1/2" 2"	HY10 HY12 HY16	\$23.25 27.50 32.00

Note: Stem has a collar behind the hex to engage fingers

Note: Stem has a collar behind the hex to engage fingers

Clamps for Wire Braid or Spiral Ply Hose



2-bolt Clamps for 1 Wire Hose

 Hose I.D.	O.D. Range	Part #	Price/Ea	Torque
3/8"	48/64" - 50/64"	HD1-3	\$9.80	12
1/2"	56/64" - 60/64"	HD1-4	11.60	18
3/4"	1-10/64" - 1-14/64"	HD1-6	14.80	18
1"	1-29/64" - 1-35/64"	HD1-8	17.40	36



2-bolt Clamps for 2 Wire Hose

Hose I.D.	O.D. Range	Part #	Price/Ea	Torque
3/8"	52/64" - 56/64"	HD2-3	\$10.50	12
1/2"	60/64" - 1"	HD2-4	11.75	18
3/4"	1-14/64" - 1-18/64"	HD2-6	14.85	18
1"	1-33/64" - 1-39/64"	HD2-8	19.50	36

4-bolt Clamps for Hydraulic Hose with 1, 2 or 4 Wire Braids or Spiral Plies

Hose I.D.	O.D. Range	Part #	Price/ Each	Torque*
1-1/4"	1-48/64" - 2"	HD2-9	\$26.50	64
1-1/4"	2" - 2-8/64"	HD2-10~	22.25	64
1-1/2"	2-12/64" - 2-18/64"	HD2-11~	23.30	64
1-1/2"	2-16/64" - 2-20/64"	HD2-12~	23.30	64
2"	2-36/64" - 2-48/64"	HD2-15	37.00	90
2"	2-48/64" - 2-58/64"	HD2-16	37.00	90
* Dooom	monded Torque Pating	in Et/l be		

Recommended Torque Rating in Ft/Lbs.

Hydraulic Hose Clamps

- Plated malleable iron
- Le-Hi style hydraulic hose clamps are for use only on 1 or 2 wire hydraulic hoses that have outside diameters that fall within recommended ranges as shown in this catalog.
- This clamp should not be used on 4 or 6 wire hydraulic hose even when hose falls within recommended ranges.

Hose I.D.	O.D. Range			Plated Mall. Iron Part #	Price/ Each	Torque*	
3/8"	50/64"	-	52/64"	HRC-037	\$8.50	18	
1/2"	57/64"	-	1"	HRC-050	13.60	18	
3/4"	1-16/64"	-	1-20/64"	HRC-075	11.70	36	
1"	1-37/64"	-	1-41/64"	HRC-100	13.00	64	
1-1/4"	1-54/64"	-	1-62/64"	HRC-125	22.25	90	
1-1/2"	2-10/64"	-	2-18/64"	HRC-150	24.00	90	
2"	2-43/64"	-	2-52/64"	HRC-200	28.75	90	
* Recommended Torque Rating in Ft/Lbs.							



Hydraulic Pipe Swivel Adapters

Dixon pipe swivel adapters are designed to prevent hose stress due to twisting during assembly. Their compact design also provides ease of assembly, particularly in confining areas. The female NPSM swivel seals by means of a 30° seat. The mating male pipe must have a 30° chamfer in order to seal. Zinc plated steel. Female



Male Pipe x









Female Pipe x **Female Pipe Swivel Nut**

-			
Male NPTF	Female NPSM	Part #	Price / Each
1/8"	1/8"	1404-2-2	\$1.85
1/8"	1/4"	1404-2-4	2.90
1/4"	1/4"	1404-4-4	2.30
1/4"	3/8"	1404-4-6	3.25
3/8"	1/4"	1404-6-4	3.65
3/8"	3/8"	1404-6-6	3.25
3/8"	1/2"	1404-6-8~	4.20
1/2"	3/8"	1404-8-6	4.80
1/2"	1/2"	1404-8-8	3.95
1/2"	3/4"	1404-8-12	7.20
3/4"	1/2"	1404-12-8	6.20
3/4"	3/4"	1404-12-12	6.45
1"	1"	1404-16-16	9.95
1-1/4"	1-1/4"	1404-20-20	16.00
1-1/2"	1-1/2"	1404-24-24	21.85
2"	2"	1404-32-32~	41.95

Female Pipe Swivel Nut							
Female NPTF	Female NPSM	Part #	Price / Each				
1/8"	1/8"	1405-2-2	\$2.50				
1/4"	1/4"	1405-4-4	2.50				
3/8"	3/8"	1405-6-6	3.30				
1/2"	1/2"	1405-8-8	4.10				
3/4"	3/4"	1405-12-12	6.55				
1"	1"	1405-16-16	10.15				
1-1/4"	1-1/4"	1405-20-20	17.15				
1-1/2"	1-1/2"	1405-24-24	21.85				
2"	2"	1405-32-32	44.50				





90° Male Pipe x Female Pipe Swivel Nut


Female NPSM Female NPTF

90° Female Pipe x Female Pipe Swivel Nut

Male NPTF	Female NPSM	Part #	Price / Each	Female NPTF	Female NPSM	Part #	Price / Each
1/8"	1/8"	1501-2-2	\$3.60				
1/4"	1/4"	1501-4-4	3.80	1/4"	1/4"	1502-4-4~	\$5.00
3/8"	3/8"	1501-6-6	5.40	3/8"	3/8"	1502-6-6	5.75
1/2"	1/2"	1501-8-8	6.75	1/2"	1/2"	1502-8-8	7.50
3/4"	3/4"	1501-12-12	11.35				
1"	1"	1501-16-16	17.20				

Hydraulic Pipe Plugs







Male Plugs



Male Plugs

lale Pipe Threads	Part #	Price / Each	Male JIC Screw Thread	Part #	Price / Each	SAE O-Ring Boss Thread	Part #	Price / Each
1/4"-18	1251-04H	\$1.00	7/16"-20	1254-04H	\$.90	7/16" - 20	1255-04H	\$1.10
3/8"-18	1251-06H	1.20	9/16"-18	1254-06H	.90	9/16" - 18	1255-06H	1.20
1/2"-14	1251-08H	1.70	3/4"-16	1254-08H	1.65	3/4" - 16	1255-08H	1.65
3/4"-14	1251-12H	3.40	7/8"-14	1254-10H	2.50	7/8" - 14	1255-10H	2.10
"-11-1/2	1251-16H	5.90	1-1/16"-12	1254-12H	3.30	1-1/16" - 12	1255-12H	3.00
			1-5/16"-12	1254-16H	5.25	1-5/16" - 12	1255-16H	5.10

Н

1"

Hydraulic Pipe Adapters



Male x Male



90° Male x Male

Male SAE Screw Thread	Part #	Price / Each	Male SAE Screw Thread	Part #	Price / Each
7/16"-20	1204-04-04	\$1.40	7/16"-20	1234-04-04	\$2.50
9/16"-18	1204-06-06	1.55	9/16"-18	1234-06-06	3.30
3/4"-16	1204-08-08	2.30	3/4"-16	1234-08-08	4.00
7/8"-14	1204-10-10	2.95	7/8"-14	1234-10-10	5.80
1-1/16"-12	1204-12-12	4.40	1-1/16"-12	1234-12-12	9.60
1-5/16"-12	1204-16-16	5.65	1-5/16"-12	1234-16-16	14.00



45° Male x Male

SAE O-Ring Boss Thread	Male SAE Screw Thread	Part #	Price / Each
7/16"-20	7/16"-20	1240-04-04	\$4.10
9/16"-18	9/16"-18	1240-06-06	5.25
9/16"-18	3/4"-16	1240-06-08	6.40
3/4"-16	9/16"-18	1240-08-06	7.50
3/4"-16	3/4"-16	1240-08-08	6.90
3/4"-16	7/8"-14	1240-08-10	8.65
7/8"-14	3/4"-16	1240-10-08	9.00
7/8"-14	7/8"-14	1240-10-10	8.50
1-1/16"-12	1-1/16"-12	1240-12-12	11.30
1-5/16"-12	1-5/16"-12	1240-16-16	17.10
	Boss Thread 7/16"-20 9/16"-18 9/16"-18 3/4"-16 3/4"-16 3/4"-16 7/8"-14 7/8"-14 1-1/16"-12	Boss ThreadScrew Thread7/16"-207/16"-209/16"-189/16"-189/16"-183/4"-163/4"-169/16"-183/4"-163/4"-163/4"-167/8"-147/8"-143/4"-167/8"-147/8"-141-1/16"-121-1/16"-12	Boss ThreadScrew ThreadPart #7/16"-207/16"-201240-04-049/16"-189/16"-181240-06-069/16"-183/4"-161240-06-083/4"-169/16"-181240-08-063/4"-163/4"-161240-08-083/4"-167/8"-141240-08-083/4"-167/8"-141240-08-107/8"-143/4"-161240-10-087/8"-141/8"-141240-10-101-1/16"-121-1/16"-121240-12-12



 90° Male x Male

SAE O-Ring Boss Thread	Male SAE Screw Thread	Part #	Price / Each
7/16"-20	7/16"-20	1238-04-04	\$3.50
7/16"-20	9/16"-18	1238-04-06	4.20
9/16"-18	7/16"-20	1238-06-04	4.40
9/16"-18	9/16"-18	1238-06-06	3.80
3/4"-16	9/16"-18	1238-08-06	6.40
3/4"-16	3/4"-16	1238-08-08	5.75
3/4"-16	7/8"-14	1238-08-10	7.20
7/8"-14	3/4"-16	1238-10-08	7.00
7/8"-14	7/8"-14	1238-10-10	8.10
1-1/16"-12	1-1/16"-12	1238-12-12	10.50
1-5/16"-12	1-5/16"-12	1238-16-16	16.00



Male x Male

SAE O-Ring Boss Thread	Male SAE Screw Thread	Part #	Price / Each
7/16"-20	7/16"-20	1231-04-04	\$1.20
7/16"-20	9/16"-18	1231-04-06	1.75
9/16"-18	7/16"-20	1231-06-04	1.95
9/16"-18	9/16"-18	1231-06-06	1.40
9/16"-18	3/4"-16	1231-06-08	2.15
3/4"-16	9/16"-18	1231-08-06	2.75
3/4"-16	3/4"-16	1231-08-08	2.15
3/4"-16	7/8"-14	1231-08-10	2.85
7/8"-14	3/4"-16	1231-10-08	3.20
7/8"-14	7/8"-14	1231-10-10	2.60
7/8"-14	1-1/16"-12	1231-10-12	4.45
1-1/16"-12	7/8"-14	1231-12-10	4.70
1-1/16"-12	1-1/16"-12	1231-12-12	4.05
1-5/16"-12	1-5/16"-12	1231-16-16	4.65

SAE (JIC) 37° Hydraulic Adapters

Zinc plated steel

• Other shapes and sizes are available on special order. Consult factory for price and availability.

Male NPTF	Male JIC	Part #	Price / Each	
1/8"	7/16"-20	2404-4-2	\$.95	
1/4"	7/16"-20	2404-4-4	1.25	
1/4"	9/16"-18	2404-6-4	1.30	
3/8"	9/16"-18	2404-6-6	1.80	
3/8"	3/4"-16	2404-8-6	1.85	
1/2"	3/4"-16	2404-8-8	2.25	
1/2"	7/8"-14	2404-10-8	2.75	
3/4"	1-1/16"-12	2404-12-12	3.90	

Male Pipe x Male 37°JIC

Female Pipe x Male 37° JIC

Female NPTF	Male JIC	Part #	Price / Each
1/8"	7/16"-20	2405-4-2	\$1.65
1/4"	7/16"-20	2405-4-4~	2.75
1/4"	9/16"-18	2405-6-4~	2.15
3/8"	9/16"-18	2405-6-6~	2.85
3/8"	3/4"-16	2405-8-6~	2.75
1/2"	3/4"-16	<i>2405-8-8~</i>	3.90
1/2"	7/8"-14	2405-10-8~	4.00
3/4"	1-1/16"-12	2405-12-12~	5.75

45° Male Pipe x Male 37° JIC

	Male JIC	Part #	Price / Each			
	7/16"-20	2503-4-2~	\$3.20	Male	A high	
	7/16"-20	2503-4-4	3.50	JIC	Milling Strangener	
	9/16"-18	2503-6-4	3.90	010		Male
	9/16"-18	2503-6-6	4.50		Prototetter .	NPTF
	3/4"-16	2503-8-6	4.75		Commune	
	3/4"-16	<i>2503-8-8~</i>	5.90			
	7/8"-14	2503-10-8~	6.10			
· ·	1-1/16"-12	2503-12-12	8.60			

90° Male Pipe x Male 37° JIC

		-	
Male NPTF	Male JIC	Part #	Price / Each
1/8"	7/16"-20	2501-4-2~	\$2.75
1/4"	7/16"-20	2501-4-4~	3.10
1/4"	9/16"-18	2501-6-4	2.95
3/8"	9/16"-18	2501-6-6	4.10
3/8"	3/4"-16	2501-8-6	4.20
1/2"	3/4"-16	2501-8-8	5.25
1/2"	7/8"-14	2501-10-8~	5.55
3/4"	1-1/16"-12	2501-12-12	8.50





Female

NPTF

Male JIC

Male

JIC