

Reelcraft® 5000 Series Spring Driven Hose Reels


With Hose

| Part # | Hose I.D. | Hose Length | Service | PSI | Weight | Price |
|--------|-----------|-------------|-------------|-----|--------|----------|
| 5450LP | 1/4" | 50' | Air / Water | 300 | 26 | \$554.00 |
| 5635LP | 3/8" | 35' | Air / Water | 300 | 25 | 526.00 |
| 5650LP | 3/8" | 50' | Air / Water | 300 | 37 | 629.00 |

Without Hose

| Part # | Hose Capacity | Service | PSI | Weight | Price |
|--------|----------------------------|-------------|-----|--------|----------|
| 5600LP | 50' of 1/4" or 35' of 3/8" | Air / Water | 500 | 21 | \$454.00 |
| 5605LP | 50' of 3/8" | Air / Water | 500 | 31 | 523.00 |

- Maximum temperature is **150°F**
- Reel inlet 3/8" NPTF
- All steel construction
- Full full shaft and swivel
- Furnished standard with PVC hose
- Compressed air hose should not be converted to oxygen service. Compressed air hoses are often contaminated with an oil coating, which can react explosively when oxygen is introduced.



Reelcraft® 7000 Series Spring Driven Hose Reels


With Hose

| Part # | Hose I.D. | Hose Length | Service | PSI | Weight | Price |
|--------|-----------|-------------|-------------|-----|--------|----------|
| 7670LP | 3/8" | 70' | Air / Water | 300 | 50 | \$840.00 |
| 7850LP | 1/2" | 50' | Air / Water | 300 | 51 | 820.00 |

Without Hose

| Part # | Hose Capacity | Service | PSI | Weight | Price |
|---------|----------------------------|-------------|------|--------|----------|
| 7800LP | 70' of 3/8", 50' of 1/2" | Air / Water | 500 | 43 | \$662.00 |
| 7800MP | 50' of 3/8" or 50' of 1/2" | Oil | 3000 | 44 | 765.00 |
| 7600HP~ | 50' of 1/4" or 50' of 3/8" | Grease | 5000 | 46 | 884.00 |

- All steel construction
- "LP" Low Pressure reels:
 - Maximum temperature **150°F**
 - Reel inlet 1/2" NPTF
 - PVC hose is standard
- "MP" Medium Pressure reels:
 - Maximum temperature **210°F**
 - Reel inlet 1/2" NPTF
 - SAE 100 R1T 1-wire braid hose standard
- "HP" Low Pressure reels:
 - Maximum temperature **210°F**
 - Reel inlet 1/4" NPTF
 - SAE 100 R2T 2-wire braid hose standard



Reelcraft® 80000 Series Spring Driven Hose Reels

With Hose

| Part # | Hose I.D. | Hose Length | Service | PSI | Weight | Price |
|----------|-----------|-------------|-------------|-----|--------|-----------|
| 82075LP~ | 1/2" | 75' | Air / Water | 300 | 90 | \$1211.00 |
| 82100LP | 1/2" | 100' | Air / Water | 300 | 99 | 1263.00 |
| 83050LP | 3/4" | 50' | Air / Water | 250 | 89 | 1211.00 |

Without Hose

| Part # | Hose Capacity | Service | PSI | Weight | Price |
|----------|-----------------------------|-------------|-----|--------|-----------|
| 83000LP~ | 50' of 3/4" or 100' of 1/2" | Air / Water | 500 | 74 | \$1069.00 |

- Maximum temperature is **150°F with hose**
- Maximum temperature is **210°F without hose**
- Furnished standard with PVC hose
- Reel inlet 3/4" NPTF
- Five-in-one heat treated aluminum casting incorporates main shaft, ratchet, spring arbor and inlet/outlet plumbing in one piece casting. High pressure cast steel.
- Most compact 3/4" x 50' hose reel of its capacity available.

See next page for bumper stops. Consult factory for uses other than stated services.

