

Pressure Switches Options

CODE	DESCRIPTIONS OF OPTIONS MOST COMMON OPTIONS	AVAILABILITY			
		2WPS	5WPS	6WPS	7WPS
-	No Special Features	●	●	■ ▲	■ ▲
A	Adjustable Dead Band		●	■ ▲	■ ▲
B	Bellows Actuated	●	●	■ ▲	
BD	Bellows Actuated Differential Pressure		●	■ ▲	
D	Diaphragm Actuated Diff. Pr. (DP)	●	●	■ ▲	■ ▲
E	External Pressure Adjustments		●	■ ▲	■ ▲
EE	Two External Pressure Adjustments		●	■ ▲	■ ▲
F	Flange Base Mounting			■ ●	■ ●
G	Double Diaphragm Extra Sensitive Low Pr.			■ ●	■ ●
DG	Double Diaphragm Extra Sensitive Low Differential Pressure (DP)			■ ●	■ ●
J	Safety Seal			■ ▲	■ ▲
L	One Indicator Light (Not on X Housing)		●	■	■
LL	Two Indicator Lights (Not on X Housing)		●	■	■
M	Male Pipe Mounting 1/2" NPT	●	●	■ ▲	■ ▲
O	High Overpressure Diaphragm	●	●		
P	Panel Mounting			■ ▲	■ ▲
Q	Double Snap Action (Belleville Spring)	●	●	■ ▲	
R>	Manual Reset Switch on Increase Pressure		●	■ ▲	■ ▲
R<	Manual Reset Switch on Decrease Pressure		●	■ ▲	■ ▲
SS	Special Trim Base 316 Stainless Steel	●		■ ▲	■ ▲
SI	Special Trim Base Teflon (Not on X Switches)	●		■	■
SY	Special Trim Base PVC (Not on X Switches)	●		■	■
T	Teflon Protected Diaphragm	●	●	■ ▲	■ ▲
V	High Temperature Service	●	●	■	■
Z	Viton Diaphragm	●	●	■ ▲	■ ▲

Note: Options may vary from none (-) to whatever may be required for a particular application. Options can be combined with the exception of similar types, i.e. SS & SI may not be combined.

■ - Options available on CSA Certified switches used in NEMA 4 & 12, as well as General Purpose Application.

▲ - Options available on CSA Certified switches used in Class 1, Group C&D; Class II, Groups E, F&G hazardous locations.



Corporate Office: 121 Railside Road • Toronto • ON • M3A 1B2 • (416) 444-2345 • Fax: (416) 444-8979

U.S.A. Office: 600 Ensminger Road • Buffalo • NY • 14150 • (716) 874-8700 • Fax: (716) 874-8800

www.winters.com • 1-800-WINTERS (946-8377)

12/02