

The Complete Line of Jefferson Solenoid Valves



Over 2000 of Today's Most Popular Applications



www.jeffersonvalves.com

Jefferson Solenoid Valves designs and manufactures world class solenoid valves to meet the highest demands of today's markets. 2 to 5 ways. Complete range of body and seal materials Explosion proof housings. UL and CSA approved. ISO 9001 Certified. Custom designs available.

	<p>General Service Solenoid Valves</p> <p>Direct Acting and Pilot Operated, Normally Open and Normally Closed. Brass or Stainless Steel Bodies 1/8" to 3". Wide Range of Pressure, sizes and resilient material.</p> <p>Industrial Application included: Car Wash, Air Compressors, Laundry Equipment Pumps, Industrial Water Control.</p>	<table border="1"> <thead> <tr> <th>Part #</th> <th>Size</th> </tr> </thead> <tbody> <tr><td>2026BA221T</td><td>1/8"</td></tr> <tr><td>2026BA222T</td><td>1/4"</td></tr> <tr><td>1327BA222T</td><td>1/4"</td></tr> <tr><td>2036BA03T</td><td>3/8"</td></tr> <tr><td>2036BA04T</td><td>1/2"</td></tr> <tr><td>2036BA06T</td><td>3/4"</td></tr> <tr><td>2036BA08T</td><td>1"</td></tr> <tr><td>1342BA12T</td><td>1 1/2"</td></tr> <tr><td>1342BA16T</td><td>2"</td></tr> <tr><td>1342BA20T</td><td>2 1/2"</td></tr> <tr><td>1342BA24T</td><td>3"</td></tr> </tbody> </table>	Part #	Size	2026BA221T	1/8"	2026BA222T	1/4"	1327BA222T	1/4"	2036BA03T	3/8"	2036BA04T	1/2"	2036BA06T	3/4"	2036BA08T	1"	1342BA12T	1 1/2"	1342BA16T	2"	1342BA20T	2 1/2"	1342BA24T	3"																			
Part #	Size																																												
2026BA221T	1/8"																																												
2026BA222T	1/4"																																												
1327BA222T	1/4"																																												
2036BA03T	3/8"																																												
2036BA04T	1/2"																																												
2036BA06T	3/4"																																												
2036BA08T	1"																																												
1342BA12T	1 1/2"																																												
1342BA16T	2"																																												
1342BA20T	2 1/2"																																												
1342BA24T	3"																																												
 	<p>Steam and Hot Water Valves</p> <p>Normally Closed and Normally Open. 1/8" to 3". Handle the challenges of High-temperature Fluids PTFE and EPDM discs, stainless steel seats, plus high temperature coils, help provide long, reliable service life. Mountable in any position.</p> <p>Industrial Application included: Laundries, Molding, Steam atomization, Sterilizer, Autoclaves and Many Others.</p>	<table border="1"> <tbody> <tr> <td rowspan="10" style="writing-mode: vertical-rl; transform: rotate(180deg);">Hot Water</td> <td>2026BE221T</td> <td>1/8"</td> </tr> <tr><td>2026BE222T</td><td>1/4"</td></tr> <tr><td>1324BE222T</td><td>1/4"</td></tr> <tr><td>1335BE3T</td><td>3/8"</td></tr> <tr><td>1335BE4T</td><td>1/2"</td></tr> <tr><td>1335BE6T</td><td>3/4"</td></tr> <tr><td>1342BE8T</td><td>1"</td></tr> <tr><td>1342BE12T</td><td>1 1/2"</td></tr> <tr><td>1342BE16T</td><td>2"</td></tr> <tr><td>1342BE20T</td><td>2 1/2"</td></tr> <tr><td>1342BE24T</td><td>3"</td></tr> <tr> <td rowspan="10" style="writing-mode: vertical-rl; transform: rotate(180deg);">Steam - 356° F</td> <td>1327BT222T</td> <td>1/4"</td> </tr> <tr><td>1390BT2T</td><td>1/4"</td></tr> <tr><td>1390BT4T</td><td>1/2"</td></tr> <tr><td>1342BT6T</td><td>3/4"</td></tr> <tr><td>1342BT8T</td><td>1"</td></tr> <tr><td>1342BT12T</td><td>1 1/2"</td></tr> <tr><td>1342BT16T</td><td>2"</td></tr> <tr><td>1342BT20T</td><td>2 1/2"</td></tr> <tr><td>1342BT24T</td><td>3"</td></tr> </tbody> </table>	Hot Water	2026BE221T	1/8"	2026BE222T	1/4"	1324BE222T	1/4"	1335BE3T	3/8"	1335BE4T	1/2"	1335BE6T	3/4"	1342BE8T	1"	1342BE12T	1 1/2"	1342BE16T	2"	1342BE20T	2 1/2"	1342BE24T	3"	Steam - 356° F	1327BT222T	1/4"	1390BT2T	1/4"	1390BT4T	1/2"	1342BT6T	3/4"	1342BT8T	1"	1342BT12T	1 1/2"	1342BT16T	2"	1342BT20T	2 1/2"	1342BT24T	3"	
Hot Water	2026BE221T	1/8"																																											
	2026BE222T	1/4"																																											
	1324BE222T	1/4"																																											
	1335BE3T	3/8"																																											
	1335BE4T	1/2"																																											
	1335BE6T	3/4"																																											
	1342BE8T	1"																																											
	1342BE12T	1 1/2"																																											
	1342BE16T	2"																																											
	1342BE20T	2 1/2"																																											
1342BE24T	3"																																												
Steam - 356° F	1327BT222T	1/4"																																											
	1390BT2T	1/4"																																											
	1390BT4T	1/2"																																											
	1342BT6T	3/4"																																											
	1342BT8T	1"																																											
	1342BT12T	1 1/2"																																											
	1342BT16T	2"																																											
	1342BT20T	2 1/2"																																											
	1342BT24T	3"																																											
		<p>Fuel Shut Off Valves</p> <p>Above Ground Storage Fuel Tank, Fuel Lines. Direct Acting. Normally Closed. 1/8" to 3". Suitable for ambient Temperature up to 175° F</p> <p>Industrial Application included: For pilot and main line commercial industrial fuel, diesel oil burner.</p>	<table border="1"> <tbody> <tr><td>2026BV221T</td><td>1/8"</td></tr> <tr><td>2026BV222T</td><td>1/4"</td></tr> <tr><td>1327BV222T</td><td>1/4"</td></tr> <tr><td>1335BV4AT</td><td>1/2"</td></tr> <tr><td>1335BV6AT</td><td>3/4"</td></tr> <tr><td>1314BV08AT</td><td>1"</td></tr> <tr><td>1314BV12AT</td><td>1 1/2"</td></tr> <tr><td>1314BV16AT</td><td>2"</td></tr> <tr><td>1314BV24AT</td><td>3"</td></tr> </tbody> </table>	2026BV221T	1/8"	2026BV222T	1/4"	1327BV222T	1/4"	1335BV4AT	1/2"	1335BV6AT	3/4"	1314BV08AT	1"	1314BV12AT	1 1/2"	1314BV16AT	2"	1314BV24AT	3"																								
2026BV221T	1/8"																																												
2026BV222T	1/4"																																												
1327BV222T	1/4"																																												
1335BV4AT	1/2"																																												
1335BV6AT	3/4"																																												
1314BV08AT	1"																																												
1314BV12AT	1 1/2"																																												
1314BV16AT	2"																																												
1314BV24AT	3"																																												
	<p>Gas Shut off Valves</p> <p>Direct Acting and Pilot Operated. Normally Closed. 1/8" to 3". Suitable for ambient Temperature up to 175° F.</p> <p>Industrial Application included: For on/off control of pilot and main line commercial industrial gas burners.</p>	<table border="1"> <tbody> <tr><td>2026BA221T</td><td>1/8"</td></tr> <tr><td>2026BA222T</td><td>1/4"</td></tr> <tr><td>1327BA222T</td><td>1/4"</td></tr> <tr><td>1330LA04T</td><td>1/2"</td></tr> <tr><td>1330LA06T</td><td>3/4"</td></tr> <tr><td>2030LA08T</td><td>1"</td></tr> <tr><td>1330LA08T</td><td>1"</td></tr> <tr><td>2030LA10T</td><td>1 1/4"</td></tr> <tr><td>2030LA12T</td><td>1 1/2"</td></tr> <tr><td>2030LA16T</td><td>2"</td></tr> </tbody> </table>	2026BA221T	1/8"	2026BA222T	1/4"	1327BA222T	1/4"	1330LA04T	1/2"	1330LA06T	3/4"	2030LA08T	1"	1330LA08T	1"	2030LA10T	1 1/4"	2030LA12T	1 1/2"	2030LA16T	2"																							
2026BA221T	1/8"																																												
2026BA222T	1/4"																																												
1327BA222T	1/4"																																												
1330LA04T	1/2"																																												
1330LA06T	3/4"																																												
2030LA08T	1"																																												
1330LA08T	1"																																												
2030LA10T	1 1/4"																																												
2030LA12T	1 1/2"																																												
2030LA16T	2"																																												
	<p>Gas Vent Valves</p> <p>Normally Open. 3/4 to 1 1/2". Die-Cast Aluminum Bodies. Direct Acting and Zero Differential Piloted Diaphragm. Suitable for ambient Temperature up to 175° F.</p> <p>Industrial Application included: Vent Valves for Commercial Burners.</p>	<table border="1"> <tbody> <tr><td>1330LA04NAT</td><td>1/2"</td></tr> <tr><td>1330LA06NAT</td><td>3/4"</td></tr> <tr><td>1330LA08NAT</td><td>1"</td></tr> <tr><td>2030LA12NAT</td><td>1 1/2"</td></tr> <tr><td>2030LA16NAT</td><td>2"</td></tr> </tbody> </table>	1330LA04NAT	1/2"	1330LA06NAT	3/4"	1330LA08NAT	1"	2030LA12NAT	1 1/2"	2030LA16NAT	2"																																	
1330LA04NAT	1/2"																																												
1330LA06NAT	3/4"																																												
1330LA08NAT	1"																																												
2030LA12NAT	1 1/2"																																												
2030LA16NAT	2"																																												
	<p>3/2 and 4/2 Ways Air and Water Solenoid Valves</p> <p>Pilot Operated and Direct Acting. 1/4" to 3/4". Diaphragm poppet valves suitable for controlling air-inert gas and liquids. Interanal piloting controls large orifices to provide high flows. Can be used to pilot large actuators to provide quick closing of large control valves. Mountable in any position.</p> <p>Industrial Application included: Single and double acting cylinders.</p>	<table border="1"> <tbody> <tr><td>1365BA17UT</td><td>1/4"</td></tr> <tr><td>1323BA17UT</td><td>1/4"</td></tr> <tr><td>1325BA4CT</td><td>1/2"</td></tr> <tr><td>1325BA4AT</td><td>1/2"</td></tr> <tr><td>1325BA3CT</td><td>1/2"</td></tr> <tr><td>1325BA3AT</td><td>1/2"</td></tr> <tr><td>1325BA6AT</td><td>3/4"</td></tr> <tr><td>1325BA6CT</td><td>3/4"</td></tr> </tbody> </table>	1365BA17UT	1/4"	1323BA17UT	1/4"	1325BA4CT	1/2"	1325BA4AT	1/2"	1325BA3CT	1/2"	1325BA3AT	1/2"	1325BA6AT	3/4"	1325BA6CT	3/4"																											
1365BA17UT	1/4"																																												
1323BA17UT	1/4"																																												
1325BA4CT	1/2"																																												
1325BA4AT	1/2"																																												
1325BA3CT	1/2"																																												
1325BA3AT	1/2"																																												
1325BA6AT	3/4"																																												
1325BA6CT	3/4"																																												

Standard Voltages: AC/60: 24V, 110V, 120V, 220V, 240V, 480V; DC: 12V, 24V, 110V, 220V.



www.jeffersonvalves.com

Jefferson Solenoid Valves USA, Inc.
20225 NE 15th CT., Miami, FL 33170
Tel: 1(305)249-8120 Fax: 1(305)249-8121
Toll Free: 1-866-42-VALVE (82583)
E-mail: info@jeffersonvalves.com